

Industrial Sewing Machine Garment Equipment

#### RIJVIN SEWING MACHINES PVT. LTD.

Address: 7, Olive Residency, Opp. Puraniks Reserva Gate, Ovale, Ghodbunder Road, Thane West, Thane - 400615.

Mobile: 9821437235 Email: sales@jvinism.com Website: www.jvinism.com




## **Production Solution**





- 1. Flat bed interlock sewing machine
- 2. Cylinder bed interlock sewing machine
- 3. Cylinder bed interlock sewing machine with left cutter
- 4. 4 thread overlock sewing machine
- 5. Collar setting machine
- 6. Tape attaching machine



1. Zigzag sewing machine

Button attaching machine

7. Shirt fronting attaching8. Pocket attaching machine

- 2. Hook and eye sewing machine for bra
- 3. Bar tacking sewing machine
- 4. Lockstitch sewing machine

## SUIT -



- 1. Lockstitch sewing machine
- 2. Hand stitch sewing machine
  3. Overlock sewing machine
  4. Button attaching machine
  5. Bar tacking machine

- 6. Eyelet button holing macgine
- Sleeve setting machine
   Automatic pocket welting sewing machine

#### DOWN COAT -



- Temple sewing machine
- Lockstitch sewing machine
- Button attaching machine
- Bar tacking sewing machine
- Overlock sewing machine

#### UNDERPANTS



- 1. Flat bed interlock sewing machine
- 2. Cylinder bed interlock sewing machine
- 3. Cylinder bed interlock sewing machine
- 4. Cylinder bed interlock sewing machine with right cutter
  5. 4 thread overlock sewing machine with elastic attaching
  6. 4 thread overlock sewing machine
  7. 4 thread overlock sewing machine

- 7. Bar tacking sewing machine for joining



## **Production Solution**

















### **Direct Drive Single Needle Lockstitch Sewing Machine**





1-needle stitch

Light	Medium	Heavy

- Latest model of direct drive lockstitch machine
- With automatic needle positioning
- Most stable control & motor
- Bright LED light
- Equipped with direct-drive servo motor, it can save 70% electricity.
- Lower noise, without radiation, the machine is applicable for different materials, and with its advanced noise- decreasing device, it remains its reliability and durability at the high speed of 5000r/min.
- Improves the efficiency.


Model No.	JN-J4
Description	Direct Drive Single Needle Lockstitch Sewing Machine
Max. Speed	5,000sti/min
Lubrication	Automatic
Needle Type	DBX1 (#14)
Max. Stitch Length	5mm or 7mm if required
Needle Bar Stroke	30.7mm
Pesser Foot Lift	By hand: 5.5mm; By knee: 13mm
Bobbin Thread Winder	Built-in the machine head
Power	550W
G/N Weight & Volume	36/31kgs, 650*245*530mm
Complete Set	With stand & table 64kgs, 0.15cbm

JN-Z2



### **Direct Drive Single Needle Lockstitch Sewing Machine with Edge Cutter**





1-needle stitch

Light	Medium	Heavy

- New design of touch-screen display clearly, operating easily, no dead angle.
- Voice prompts, operating conveniently.
- Chinese or english. can be switched easily.
- With needle replacement function.
- With usb connection. charging electronic products.
- Design of universal shaft drive, improve efficiency, not easy to wear improve ab coupling
- With convenient separating button of knife, integrated knife structure side-cutter Could be switch freely, one machine with dual-purpose.

Model No.	JN-Z2
Description	Direct Drive Single Needle Lockstitch Sewing Machine with Edge Cutter
Max. Speed	5,000sti/min
Lubrication	Automatic
Needle Type	DBX1 7#-16#
Max. Stitch Length	5mm or 7mm if required
Needle Bar Stroke	30.7mm
Presser Foot Lift	By hand: 5.5mm; By knee: 13mm
Bobbin Thread Winder	Built-in the machine head
Power	550W
G/N Weight & Volume	36/31kgs, 650*245*530mm
Complete Set	With stand & table 64kgs, 0.15cbm

## JN-0303-D4



### **Direct Drive Integrated Top & Bottom Feed Lockstitch Sewing Machine**



- With the character of quick start and precise stop lower noise and vibration, the machine the energy consumption as much as 35%, compared with the ordinary clutch motor machi better panel, operation is more simple, convenient, greatly improving the work eiciency bu 15%` incomparison of the ordinary clutch motor machines. Stitch compensation function in! FIT special materials and requirement.
- Big hook and big bobbin can save times in changing t for winding thread.


Model No.	JN-0303-D4
Description	Direct Drive Integrated Top & Bottom Feed Lockstitch Sewing Machine
Max. Speed	2500RPM
Needle Type	DPx5 16#-20#
Max. Stitch Length	12MM
Presser Foot Lift	7-16MM
G/N Weight & Volume	27.5/33.5 KGS 580*250*530MM
Complete Set	51.5/59.5KGS

JN-N2



## **Computerised Direct Drive 2 Function UBT Machine**





Light	Medium	Heavy
	1	

- Automatic thread trimmer
- Automatic needle positioning & reverse stitching
- Electronic thread tension & LED light


Model No.	N2
Description	Direct Drive Computerised Single Needle 2 Function UBT Machine
Max. Speed	5,000sti/min
Lubrication	Automatic
Needle Type	DBX1 7#-16#
Max. Stitch Length	5mm or 7mm if required
Needle bar stroke	30.7mm
Presser Foot Lift	By hand: 5.5mm; By knee: 13mm
Bobbin Thread Winder	Built-in the machine head
Power	550W
G/N Weight & Volume	36/31kgs, 650*245*530mm
Complete Set	With stand & table 64kgs, 0.15cbm

JN-N3



## **Computerised Direct Drive 3 Function UBT Machine**





1-needle lockstitch

Light	Medium	Heavy
		to the first term


- Automatic thread trimmer
- Automatic needle positioning & reverse stitching
- Electronic thread tension & LED light

Model No.	N3
	Direct Drive Computerised Single Needle Full Function UBT
Description	Machine with Auto Tread Trimmer and Reverse Stitch
	(For Both Light and Heavy Duty, Colling Fan, Humanised Design.)
Max. Speed	5,000sti/min
Lubrication	Automatic
Needle Type	DBX1 7#-16#
Max. Stitch Length	5mm or 7mm if required
Needle Bar Stroke	30.7mm
Pesser Foot Lift	By hand: 5.5mm; By knee: 13mm
Bobbin Thread Winder	Built-in the machine head
Power	550W
G/N Weight & Volume	36/31kgs, 650*245*530mm
Complete Set	With stand & table 64kgs, 0.15cbm



### **Computerised Direct Drive 4 Function UBT Machine**





1-needle lockstitch

Light	Medium	Heavy
The second second		

- Computerized control system and servo motor
- Automatic thread trimmer & foot lifter
- Automatic needle positioning & reverse stitching
- Electronic thread tension & LED light

Model No.	N4	
Description	Direct Drive Computerised Single Needle Full Function UBT	
	Machine with Auto Tread Trimmer, Auto Reverse Stitch,	
	Electronic Thread tension for heavy, medium and light fabrics	
	with start sensor and Auto Foot Lifter (For Both Light and Heavy	
	Duty, Colling Fan, Touch-Tone Factory Reset, Humanised Design.)	
Max. Speed	5,000sti/min	
Lubrication	Automatic	
Needle type	DBX1 7#-16#	
Max. Stitch Length	5mm or 7mm if required	
Needle Bar Stroke	30.7mm	
Presser Foot Lift	By hand: 5.5mm; By knee: 13mm	
Bobbin Thread Winder	Built-in the machine head	
Power	550W	
G/N Weight & Volume	36/31kgs, 650*245*530mm	
Complete Set	With stand & table 64kgs, 0.15cbm	

## JN-V3-4



## V3-4 (Direct Drive 4 Thread Overlock Sewing Machine)





4 thread

Light	Medium	Heavy

- Super high speed with maximum at 7000 rpm
- Fabric thickness sensor to control thread trimming length
- Working well for light to medium heavy material
- Bright LED light

Model No.	V3-4/5
Description	Direct Drive 4 Thread and 5 Thread Overlock Sewing Machine
Needle Number	2/3
Threads Number	4/5
Max. Speed	6,000/5,500sti/min
Needle Type	9#
Max. Stitch Length	0.5-3.8MM
Max. Stitch Width	6MM/5MM
Pesser Foot Lift	5.5MM
G/N Weight & Volume	29/36KGS 455*335*535MM
Complete Set	53/62KGS 0.15CBM

## JN-V3-5



### V3-4 (Direct Drive 4 Thread Overlock Sewing Machine)





Light	Medium	Heavy
1 1 1		

- Super high speed with maximum at 7000 rpm
- Fabric thickness sensor to control thread trimming length
- Working well for light to medium heavy material
- Bright LED light

Model No.	V3-5
Description	Direct Drive 5 Thread Overlock Sewing Machine
Needle Number	3
Threads Number	5
Max. Speed	5,500sti/min
Needle Type	9#
Max. Stitch Length	0.5-3.8MM
Max. Stitch Width	5MM
Pesser Foot Lift	5.5MM
G/N Weight & Volume	29/36KGS 455*335*535MM
Complete Set	53/62KGS 0.15CBM


## JN-V4-D



### **High Speed Flatbed Direct Drive Interlock Sewing Machine**







- Suitable for big area fabric sewing, sew decoration stitches on both surface of fabric,
- And sew many kinds of decoration.
- Adopt to small size servo motor intstead of traditional strap.
- Can start to work or stop quickly, shorten transmission route, upgrade the precision.
- Reduce any malfunction to minimum during sewing in order to sew top qualtiy stitches.
- Direct drive servo motor.
- Automatic needle positioning.


Model No.	V4-D
Description	Direct Drive Interlock Sewing Machine
Max. Speed	5000RPM
Needle Number	3
Threads Number	5
Needle Type	UY128GAS 11#
Max. Stitch Length	1.5-4.5MM
Needle Gauge	5.6/6.4
Presser Foot Lift	5.5-7MM
G/N Weight & Volume	50/57KGS 660*395*630MM
Complete Set	74/83KGS 0.23CBM

## JN-1377D



## **Direct Drive Button Attaching Machine**





- Difference in Knot-Tying Methods
- Compare with formerly button attaching mode, the brand new greatly reduce losening of thread this Phenomenon.
- Quick Stitch-Shape Changing Function.
- Stitch Shape can easily be changed over among.
- Button Attach configuration only by operating the lever.

Model No.	JN-1377D
Description	Direct Drive Button Attaching Machine
Max. speed	1500RPM
K	
$\odot$	10-28
Needle Type	TQX7 18#-20#
Pesser Foot Lift	>9MM
G/N Weight & Volume	26/30KGS 500*300*400
Complete Set	48/54KGS 0.13CBM


## JN-781D



### High speed direct drive button holing sewing machine







- This machine have auto foot lifter and auto trimming function.
- This makes the machine more stable and less noise.
- It's suitable for all light and medium materials, and capable of forming two different types stitches, namely flat stitch and triangle stitch.
- The stitches are irm and beautiful.
- Adjustable buttonhole length and width.

Model No.	JN-781D
Description	Direct Drive Button Hole Machine
Max. Speed	3600RPM
Needle Type	DPX5 11#~14#
Max. Stitch Length	22MM
Max. Stitch Width	2.5-4MM
Presser Foot Lift	12MM
G/N Weight & Volume	58/69KGS 745*340*930MM
Complete Set	82/95 KGS 032CBM

## JN-1790



### **Computerised Electronic Button Hole Machine**



- Using step motor in feed mechanism and needle mechanism, the minimum incremen can reach 0.05mm. to realize Perfect and stitch.
- It is possible to set sewing speed to front 5 stitch by panel to realize low speed switch on function to avoid Thread.
- With electrical control.
- For the final several stitches when bar tacking which can precent the thread of from the buttonhole.

Model No.	JN-1790
Description	Computerised Electronic Button Hole Machine
Max. Speed	4200RPM
Needle Type	DPX5 11#~14#
Max. Stitch Length	25MM
Max. Stitch Width	2.5-4MM
Presser Foot Lift	17MM
G/N Weight & Volume	110/120KGS 780*390*765MM
Complete Set	134/148KGS 0.3CBM

## JN-9820



### **Direct Drive Computer Controlled Eyelet Button Hole Sewing Machine**











- Enhanced productivity with the world's highest max.sewing speed 2500rpm.
- Fine stitches with high-precision stitch point.
- Large arm pocket allowing smooth material handling.
- Easy-to-use operation panel

Model No.	JN-9820
Description	Direct Drive Computer Controlled Eyelet Button Hole Sewing Machine
Max. Speed	1000-2500RPM
Stitch Pitch	0.5-2.0MM
Presser Foot Lift	12MM as Standard (Available upto 16MM)
Needle Type	DOX588 (Nm80 - Nm120)
Air Pressure	0.5Mpa
G/N Weight & Volume	230/250 KGS 1250*800*1300


## JN-1903A



### **Computerised Control Electronic Button Feeding Attaching Machine**



- High eficiency`
- High precision and stable work
- Humanity and easy operation
- Intellect monitor and adjustment




Model No.	JN-1903A
Description	Computerised Control Electronic Button Feeding Attaching Machine
Max. Speed	3000RPM
Needle Type	DPX17(14#)
Presser Foot Lift	13MM
G/N Weight & Volume	100/110KGS 730*330*700
Complete Set	124/136KGS 0.24KGS

## JN-1900ASS



### **Computerised Electronic Bartacking Machine**







Touch-screen display is for optional

- It is applicable to sew bar tacks at garment's parts where needs enforced.
- By controlling operation panel, you can select required sewing speed, sewn patterns and increase or reduce seam size.
- Special patterns are also can be realized such as umbrella circular track and suit's decorative button hole.
- As a result of computer direct drive, the machine claims rapid engines start and stop.
- Compared with machine of traditional model, it shortens the time by 35%, hence a further increase in production efficiency.

Model No.	JN-1900ASS
Max. Speed	3,000sti/min
Bar Tacking Size	X=40mm Y=30mm
Stitch Length	0.1-12.7mm (0.1mm per step)
Needle Bar Stroke	45.7mm
Presser Lifter Height	17mm
Needle Type	DPX5 14#
Lubrication	Automatic
Storage Capacity	200,000 stitches as max
Stored Patterns	200 patterns as max
Scale Up & Down Function	20-200%
Motor Power	550W
G/N Weight & Volume	65/60kgs, 800^380^800mm=0.243cbm
Complete Set	With stand & table 93kgs, 0.33cbm

# JN-3800D-1/2/3



#### **Direct Drive Chain Stitch Machine Series**



- The machine operation space is large, the direct drive servo device can make the sewing speed free to adjust, adopt the needle thread take line.
- The needle thread line, form the three needle stitch, the stitch is beautiful straight, the elasticity, is suitable for different suture and the fabric of the sewing work, such as khaki and denim fabrics, and equipped with a variety of sizes of needle products to choose from. from silk to very Thick cowboy materials: built-in, external tugs, to meet different customer's needs.

Model No.	JN-3800D-1/2/3
Description	Direct Drive Chain Stitch Machine Series
Max. Speed	4500RPM
Needle Type	TVX7
Max. Stitch Length	0-4MM
Presser Foot Lift	5.5-10MM
Needle Number	1/2/3
G/N Weight & Volume	25/38KGS 610*240*570MM
Complete Set	49/64KGS 0.15CBM

# JN-9270D / JN-928D (PL)



### **High Speed Feed-Off-The-Arm Machine Series (with Puller)**









Gear puller

Rubber puller

Belt puller







MT-928-2PL

- The special structure of cantilever tubular is especially suitable for sleeves, trousers and such kind of caliber Things joint sewing.
- Both needle thread tension and bobbin thread tension have been decreased after Reinvestigation of the chainstitching mechanism.
- Furthermore, the stitch dial gauges and looper have been Dramatically improved.
- Forming beautifully finished seams and preventing puckering.
- It is suitable for Men's suit, suit-dress, shirts, work suits, jeans tent raincoats, etc.

Model No.	JN-9270D / JN-928D (PL)
Description	Direct Drive Feed-Off-The-Arm Machine Series (with puller)
Max. Speed	3200RPM
Needle Number	2/3
Puller Type	Gear Puller, Rubber Puller, Belt Puller
Stitch Type	Chainstitch
Needle Type	TVX64
Needle Gauge	1/4, 1/8, 3/16, 7/32
G/N Weight & Volume	47/65KGS 580*545*475MM
Complete Set	With stand & table 71kgs, 0.25cbm

## JN-2210



### **Computer Controlled Pattern Sewing Machine**









- The machine can be used in flexible pattern sewing small part sewing, various small figures and Reinforced seam and etc. the detailed sewing range involves the sewing of trademark, brand plate.
- Label, hat, waist belt chrysanthemum holes and particular bartack sewing and etc. the operation Panel uses lcd picture, which provides easy access to understanding mechanical setting or program Data input.
- Quick confirmation of data input state or thread breaking. thanks to it. the operation
  Becomes easy and workers can learn to operate machine in quite short time, thus greatly
  Shortening the worker training period.
- And the sewing machine can memory the previous figure.
- Reducing the trouble of repeated figure input.

Model No.	JN-2210
Description	Computer Controlled Pattern Sewing Machine
Max. Speed	2700RPM
Double Rotaryshuttle	2
Sewing Area	220*100MM
Needle Gauge	0.05-12.7MM
Maximum Stitch Numbers	(20,000 needles/1 pattern)
Shuttle	Twice as many shuttle(shuttle runs for options)
Motor	550W/servo motor 550W
Raisina Amount BV	22MM
Intermittent Presser Foot	
Clothar Feedingdevice	Intermittent feeding(driven by pulse motor)

## JN-T103

## JVIN®

### **Auto Sharping Cutting Machine**



Model No.	JN-T103
Description	Auto Sharping Cutting Machine
Blade Size	8 / 10 / 12 Inches
Max. Speed	2850/3400RPM
Frequency	50/60
Voltage	370V
Power	550W/750W
G/N Weight & Volume	15 KGS 660*360*260MM

## JN-RC110



### **Round Knife Cutting Machine**



Model No.	JN-RC100
Description	Round Knife Cutting Machine
Blade Dimensions	Ф100 4"
Frequency	50/60
Trimming Capacity	27
G/N Weight & Volume	15/19KGS 570*370*467MM

## JN-911



### **Strip Cutting Machine**



#### Features

The products are widely used in all kinds of circular knitted fabric, cotton, polyester cloth cut into The rolling strips and special equipment, the high degree of automation products, can effectively improve The eficiency and accuracy of cutting cloth, cloth cutting speed can be adjusted and automatic stopping Device.

Model No.	JN-911
Description	Strip Cutting Machine
Cloth Length	135MM
Edge	10-90MM
Speed	460RPM
G/N Weight & Volume	45/47KGS 162*40*47MM



### **Cloth Cutting Machine**



- Single man operation machine head automatically, the guiding trail is fitted with 4 imported mini bearing: no Swinging wire,no breaking wire avoided on the support of spring power wire point.
- It is simple to operate saving Time man power and material the balde base made of special steel is not easy to wear the high rotating speed Motor can grind the blade automatically in single direction, automatic layer counting display.
- Press the cloth Simultaneously.
- Cut off automatically to avoid the dislocation of accessory materials appropriate products:
- Textiles:cotton.line.silk.wind coat cloth raincoat cloth and others:artificial fibers nylon.
   And others.
- Plastics plastic cluth palstic film plastic leather and other.

Model No.	JN-B-1
Description	Cloth Cutting Machine
Power	160
Volage	110/220V
Frequency	50/60
Cutting Width	1.2-3.0MM
Cutting Height	9MM
Rail Length	1.6-3.6
G/N Weight & Volume	15/17KGS 760*460*200MM

## JN-110R



### **Automatic Belt Loop Cutter Machine (Cold & Hot)**



- Special features: High speed Itcan cut 95pcs per minute (50mm long) Accuracy Cut-length is accurate owing to a stepping motor Cutting type: Melting & cutting by hot knife tapes are cut neatly without fraying and installed with anti-static electricity device Automatic operation it works automatically only by setting speed length quantity and temperature.
- It stops automatically if materials run out during operation.
- Compensation After actual length data inputted accurately cut out the length meet the system settings fault self-check cutting sensor error. no supply, the error code will show on the system panel directly if the fault happened Memory: Set -length & set-speed are not erased even if power off & on band for correct length.

Model No.	JN-110R
Description	Automatic Belt Loop Cutter Machine (Cold & Hot)
Cutting Length	20-9999MM
Max. Cutting Width	95MM
Cutting Speed	95RPM
Max. Blade Temp	350 °C
Voltage	110/220V
Frequency	50/60
Power	0.64KW
G/N Weight & Volume	19/24 560*420*450M

## JN-801



### **Fully Enclosed Pilling Machine**



#### Features

The knife grinder makes the knife sharp it attached automatically bits removing equipment, the transmission of ball bearing makes the machine easy to operate low noise and wear well skiving thinner for surfaces of shoes leather shoes, handbags and gloves which made of fur leather and rubber.

Model No.	JN-801
Description	Fully Enclosed Pilling Machine
Motor Power	0.4KW
Working Voltage	110/220V
G/N Weight & Volume	41/44 Kg 620*420*420MM

## JN-801A/802A



### One/Two Reamers Make Cloth Cut Strip Machine



#### Features

This machine is a perfect tool for making cloth cut strip, the width of bias is adjustable up to 100mm, the cloth feed will be very smooth at your working this machine with single or double blade Is design.

Model No.	JN-801A/802A	
Description	One/Two Reamers Make Cloth Cut Strip Machine	
Capacity	3000	
Strip Width	0.5-4	
Motor Pully	4''-5.5"	
G/N Weight & Volume	24/25KGS 250*350*830MM	

# JN-600B



### **Fusing Machine**



- Adhesive machine is a hot melt pressurized continuous bonder.
- It has the special Performance of preventing from deviation.
- It is fit for the hot pressing adhesion to the clothing Fabrics and hot-melt lining.
- It is widely applicable for the bonding between the adhesive interlining and the collar front Breast sleeve.
- Clothing double selvage waist band etc. without the flammable agent after the Adhesion it appears to be stiff and smooth.
- It has sound durability to the cleaning.
- It is not Easy to be cockled.
- It is especiouly suitable for various resin collar interlining.non-woven Interlining bonding.

JN-600B
Fusing Machine
600mm
600×1530mm
600×1660mm
0-10m/min
0-0.15MPa
≤190°C
50W
7KW
220V/1PH/50HZ
218kg 1100×900×900mm

## JN-500G

## JVIN®

### **Staple Pin Attacher**



#### Features

- Simple and easy counting.
- Safe and easy by foot controller.
- · Suitable for different labling and attching.
- The staple pin for this Machine is made of soft polymer which makes sure the labels are tightly fastened to the garments and easy to remove without damage.

Model No.	JN-500G
Description	Staple Pin Attacher
Max. Speed	1500RPM
G/N Weight & Volume	22/25KGS 400*270*360MM

## JN-26-1A



### **Portable Bag Closure Machine**



- Simple and easy counting.
- · Safe and easy by foot controller.
- Suitable for different labling and attching.
- The staple pin for this Machine is made of soft polymer which makes sure the labels are tightly fastened to the garments and easy to remove without damage.

Model No.	JN-26-1A
Description	Portable Bag Closure Machine
Max. Speed	1250RPM
Needle Type	DNX1 25#
Stitch Length	6.5MM
G/N weight & volume	5.6/8KGS 400*270*360MM

## JN-20U43D



### **Zig Zag Sewing Machine**



- Can be in thin, medium, thick material do straight seam, curved seam, embroidery, patchwork seam.
- Cover knot seam, cover edge seam. zipper seam, cover stem seam, pattern, etc.
- The needle position Can be adjusted left. right and middle. which can form colorful decorative patterns.
- Internal winding Device, reverse feeding mechanism.

Model No.	JN-20U43D	
Description	Zig Zag Sewing Machine	
Max. Speed	2000RPM	
▼//	5mm	
¥ mm	4MM	
mm A	0-12MM	
Needle Type	DPX5	
Presser Foot Lift	6-12MM	
G/N Weight & Volume	23/28 580*250*510MM	
Complete Set	47/54KGS 0.14CBM	